

Optical Fiber Identifier



Product characteristics

- Suitable for 0.25/0.9/2.0/3.0mm Easy test directly, convenient and efficient.
- Identifies 3 common test tones.
- Small and Practical. No need to replace the chucks
- Identifies dominant traffic direction, audible alarm.
- Approximate core power reading.
- Low false detection & insertion loss.
- Very easy to operate.
- Battery low indication.

Multi-in-one fixture



3.0mm jump cable



0.9mm fiber cable



Bare fiber cable

PRODUCT SPECIFICATION:

Wavelength Recognition Range	800nm to 1700nm
Signal Recognition Type	CW,270 Hz \pm 5%,1 kHz \pm 5%,2 kHz \pm 5%
Detector Type	ϕ 1mm InGaAs 2 pcs
Adapted fiber type	Universal Holder for ϕ 0.25(Bare Fiber), ϕ 0.9, ϕ 2.0, ϕ 3.0 Cable
Signal Direction	Left & Right LED
Optical Power Reading Range	-40 dBm to 10 dBm
Signal Frequency Range	270Hz,1kHz,2kHz
Power Type	AA*2
Operating Temperature Range	-10°C to 60°C
Storage Temperature Range	-25°C to 70°C
Dimension	195mm*10mm*8mm
Weight	235g

PRODUCT LIST:

